

ステンレス(SUS304)製 パンチングメタル規格在庫表

2012年04月01日現在

パンチング種類 (Diameter X Center Pitch)			板 厚 (T=Thickness)									
金型種類 (孔 X ピッチ)	加工 No.	開孔率(%)	0.3T	0.4T	0.5T	0.6T	0.8T	1.0T	1.2T	1.5T	2.0T	3.0T
○十(ワザウ)	115-B	32.0	◎	◎	◎	◎	◎	◎	◎	◎		
0.5 X 1.09	5	19.0	◎	◎								
0.8 X 1.55	x	24.1				◎						
1.0 X 2.0	8	22.6			◎	◎	◎	◎				
1.5 X 3.0	16	22.6			◎	◎	◎	◎	◎	◎		
2.0 X 3.0	19	40.2						◎				
2.0 X 3.5	21	29.6				◎	◎	◎	◎	◎		
2.5 X 4.0	24-B	35.4						◎				
3.0 X 4.0	30	50.9			◎		◎	◎				
3.0 X 5.0	31	32.6		◎	◎	◎	◎△	◎△	◎△	◎△	◎△	
4.0 X 5.0	x	57.9						◎				
4.0 X 7.0	36	29.6				◎	◎	◎	◎	◎	◎	
5.0 X 7.0	x	46.2					◎	◎				
5.0 X 8.0	58	35.4			◎	◎	◎△	◎△	◎△	◎△	◎△	◎△
5.0 X 10.0	59	22.6						◎		◎		
6.0 X 8.0	61	50.9					◎	◎		◎		
6.0 X 9.0	60	40.2				◎	◎	◎	◎	◎	◎	
8.0 X 10.0	80	57.9				◎	◎	◎	◎	◎		
8.0 X 12.0	81	40.2						◎	◎	◎	◎	◎
10.0 X 12.5	93	57.9						◎		◎	◎	
10.0 X 15.0	92	40.2				◎	◎△	◎△	◎△	◎△	◎△	◎△
10.0 X 15.0 HL	92	40.2								◎△		
12.0 X 18.0	94-B	40.2								◎	◎	
15.0 X 20.0	95-B	50.9						◎	◎	◎	◎	
20.0 X 30.0	97	40.2								◎	◎	
長穴 3 X 12	x	39.3					◎					
長穴 3 X 20	127	43.0					◎					
3角 X 5 (並列)	188	36.0						◎				
8角 X 10(並列)	x	64.0						◎				
ステンレス在庫品表面処理・その他			BA材(脱脂処理済み)を基本としておりますが、一部 2B材, NO.1(脱脂処理無し)が含まれております。									