

鉄製 パンチングメタル規格在庫表

2012年04月01日現在

パンチング種類 (Diameter X Center Pitch)			板 厚 (T=Thickness)									
金型種類 (孔 X ピッチ)	カタログ NO.	開孔率(%)	0.5T	0.6T	0.8T	1.0T	1.2T	1.6T	2.3T	3.2T	4.5T	6.0T
○十(7/32 X 1)	115-A	32.0		○	○△	○△	○△	○△				
○十(7/32 X 1)	115-B	32.0	○	○	○△	○△	○△	○△	○△	○△		
○十(7/32 X 1)	116-B	34.0							○△			
1.0 X 2.0	8	22.6	○	○	○	○						
1.5 X 3.0	16	22.6			○	○	○					
2.0 X 3.0	19	40.2	○	○	○	○	○	○△				
2.0 X 3.5	21	29.6	○	○	○△	○△	○△	○△				
2.5 X 3.5	24	46.2		○	○	○						
2.5 X 4.0	24-B	35.4				○						
3.0 X 4.0	30	50.9	○	○	○△	○△	○△	○△				
3.0 X 5.0	31	32.6	○	○	○△	○△	○△	○△	○△	○△		
4.0 X 5.0	x	57.9				○						
4.0 X 6.0	36-A	40.2				○		○				
4.0 X 7.0	36	29.6			○	○	○△	○△	○	○		
4.5 X 6.0	x	50.9			○	○	○					
4.5 X 7.0	39	37.4			○							
5.0 X 6.0	x	62.8			○	○						
5.0 X 8.0	58	35.4	○	○	○△	○△	○△	○△	○△	○△	○	
5.0 X 10.0	59	22.6				○	○	○△	○△			
6.0 X 8.0	61	50.9			○	○	○	○△	○△			
6.0 X 9.0	60	40.2		○	○△	○△	○△	○△	○△	○△	○	
6.0 X 10.0	62	32.6									○	
8.0 X 10.0	80	57.9		○	○	○△	○△	○△	○△			
8.0 X 12.0	81	40.2			○	○△	○△	○△	○△	○△	○	
9.0 X 12.0	90	50.9						○△				
10.0 X 12.5	93	57.9			○	○	○△	○△	○△			
10.0 X 15.0	92	40.2			○△	○△	○△	○△	○△	○△	○△	○△
12.0 X 18.0	94-B	40.2						○△	○	○	○	
15.0 X 20.0	95-B	50.9				○		○				
15.0 X 22.0	x	42.0									○	○
16.0 X 21.0	96	52.5						○△	○△	○		
20.0 X 30.0	97	40.2						○△	○△	○	○	○
25.0 X 35.0	x	46.2								○		
30.0 X 40.0	99	50.9								○	○	
十 字	100	36.5				○						
十 字	x	36.0						○				
十 字	101	42.0				○	○	○				
長穴 3 X 20	127	43.0				○						
長穴 4 X 25 (並列)	x	46.0						○				
長穴 5 X 25	129	41.0						△				
菱形 8.5 X 16.5	154	40.0						○				
菱形 11 X 22	159	46.9					○	○△				
菱形 16.5 X 28	161	48.0						○				
3角 X 5 (並列)	188	36.0				○						
6角 X 9 (並列)	192	44.0				○		○△				
8角 X 10(並列)	x	64.0			○	○△	○△	○△				
10角 X 13(並列)	198	59.0				○		○△				
在庫品鉄板種類			冷延鋼板(SPCC)					酸洗鋼板(SPHC-P)		熱延鋼板(SS)		